

UH AND UB SERIES
BARRIER WASHER EXTRACTORS



SERIOUS ABOUT LAUNDRY.

UniMac[®]

UH AND UB SERIES BARRIER WASHER EXTRACTORS 18-180 KG – PROFORM AND MICRO CONTROLS

MODELS	UH180	UH240	UH280	UB265	UB332
Control	PROform	PROform	PROform	Micro	Micro
Capacity kg (lb)	18 (40)	24 (55)	28 (65)	26.5 (60)	33.2 (75)
Width mm (in)	900 (35 1/2)	1020 (40)	1130 (44 1/2)	1410 (55 1/2)	1560 (61 1/2)
Depth mm (in)	1145 (45)	1145 (45)	1145 (45)	1060 (41 3/4)	1060 (41 3/4)
Height mm (in)	1455 (57 1/4)	1455 (57 1/4)	1455 (57 1/4)	1600 (63)	1600 (63)
Number of drums	1	1	1	1	1
Number of loading doors	1	1	1	1	1
Number of unloading doors	1	1	1	1	1
Cylinder Diameter mm (in)	750 (29 1/2)	750 (29 1/2)	750 (29 1/2)	650 (25 1/2)	650 (25 1/2)
Cylinder Depth mm (in)	409 (16)	544 (21 1/2)	639 (25)	800 (31 1/2)	950 (37 1/2)
Cylinder Volume litres (Cu.ft.)	180 (6.4)	240 (8.5)	280 (65)	265 (9.4)	332 (11.7)
Door Dimensions					
Height mm (in)	325 (12 3/4)	325 (12 3/4)	325 (12 3/4)	325 (12 3/4)	325 (12 3/4)
Width mm (in)	376 (14 3/4)	496 (19 1/2)	496 (19 1/2)	496 (19 1/2)	496 (19 1/2)
Door Bottom to Floor mm (in)	655 (25 3/4)	675 (26 1/2)	670 (26 1/4)	860 (33 3/4)	860 (33 3/4)
Wash Speed RPM	42	42	42	45	45
Extract Speed RPM	939	939	914	960	960
Extract G-Force	370	370	350	335	335
Water Inlet Conn. mm (in)	3 x 19 (3/4)	3 x 19 (3/4)	3 x 19 (3/4)	3 x 25 (1)	3 x 25 (1)
Steam Inlet Conn. mm (in)	13 (1/2)	13 (1/2)	13 (1/2)	19 (3/4)	19 (3/4)
Drain Conn. Size mm (in)	76 (3)	76 (3)	76 (3)	2 x 76 (3)	2 x 76 (3)
Compressed Air Inlet mm (in)	N/A	N/A	N/A	6.4 (1/4)	6.4 (1/4)
Motor Size kW (HP)	2.20 (2.95)	3.00 (4.02)	3.00 (4.02)	4.00 (5.36)	4.00 (5.36)
Voltage/Hz/Phase	200-240V/50-60Hz/1 200-240V/50-60Hz/3 380-415/50-60Hz/3 380-415V + N/50-60Hz/3 440-480/50-60/3	200-240V/50-60Hz/1 200-240V/50-60Hz/3 380-415/50-60Hz/3 380-415V + N/50-60Hz/3 440-480/50-60/3	200-240V/50-60Hz/1 200-240V/50-60Hz/3 380-415/50-60Hz/3 380-415V + N/50-60Hz/3 440-480/50-60/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3
Shipping Dimensions mm (in)					
Height mm (in)	1610 (63 1/4)	1610 (63 1/4)	1610 (63 1/4)	1840 (72 1/2)	1840 (72 1/2)
Width mm (in)	1010 (39 3/4)	1130 (44 1/2)	1240 (49)	1465 (57 3/4)	1610 (63 1/2)
Depth mm (in)	1235 (48 1/2)	1235 (48 1/2)	1235 (48 1/2)	1175 (46 1/4)	1175 (46 1/4)
Net Weight kg (lb)	430 (950)	460 (1015)	490 (1080)	960 (2120)	1000 (2205)
Shipping Weight kg (lb)	485 (1070)	515 (1135)	550 (1215)	1070 (2360)	1090 (2405)
Agency Approvals	CE	CE	CE	CE	CE

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Czech facility has been registered to ISO 14001:2005 and 9001:2009.

UB442	UB663	UB700	UB900	UB1100	UB1400	UB1800
Micro	Micro	Micro	Micro	Micro	Micro	Micro
44.2 (100)	66.3 (150)	70 (154)	90 (198)	110 (242)	140 (308)	180 (396)
1610 (63 1/4)	2160 (85)	2025 (79 3/4)	2275 (89 1/2)	2325 (91 1/2)	2435 (96)	2585 (101 3/4)
1170 (46)	1170 (46)	1615 (63 1/2)	1615 (63 1/2)	1615 (63 1/2)	1805 (71)	1905 (75)
1650 (65)	1650 (65)	1805 (71)	1805 (71)	1855 (73)	2075 (81 3/4)	2165 (85 1/4)
1	2	1	1	1	1	1
1	2	1	1	1	1	1
1	2	1	1	1	1	1
750 (29 1/2)	750 (29 1/2)	1000 (39 1/4)	1000 (39 1/4)	1100 (43 1/4)	1200 (47 1/4)	1300 (51)
1000 (39 1/4)	2 x 750 (29 1/2)	900 (35 1/2)	1150 (45 1/4)	1200 (47 1/4)	1250 (49 1/4)	1400 (55)
442 (15.6)	663 (23.4)	700 (24.7)	900 (31.8)	1100 (38.8)	1400 (49.4)	1800 (63.6)
325 (12 3/4)	325 (12 3/4)	340 (13 1/4)	340 (13 1/4)	340 (13 1/4)	440 (17 1/4)	440 (17 1/4)
496 (19 1/2)	496 (19 1/2)	765 (30)	765 (30)	765 (30)	765 (30)	765 (30)
860 (33 3/4)	860 (33 3/4)	750 (29 1/2)	750 (29 1/2)	800 (31 1/2)	850 (33 1/2)	900 (35 1/2)
41	41	36	36	35	33	36
915	915	800	800	754	720	695
350	350	360	360	350	350	350
3 x 25 (1)	3 x 25 (1)	3 x 38 (1 1/2) + 1 x 19 (3/4)	3 x 38 (1 1/2) + 1 x 19 (3/4)	3 x 38 (1 1/2) + 1 x 19 (3/4)	3 x 38 (1 1/2) + 1 x 19 (3/4)	3 x 38 (1 1/2) + 1 x 25 (1)
19 (3/4)	19 (3/4)	25 (1)	25 (1)	25 (1)	25 (1)	25 (1)
2 x 76 (3)	2 x 76 (3)	126 (5)	126 (5)	126 (5)	126 (5)	126 (5)
6.4 (1/4)	6.4 (1/4)	10 (3/8)	10 (3/8)	10 (3/8)	10 (3/8)	10 (3/8)
7.50 (10.06)	7.50 (10.06)	11.00 (14.75)	11.00 (14.75)	15.00 (20.12)	18.50 (24.81)	22.00 (29.50)
200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3	200-240V/50-60Hz/3 380-415V/50-60Hz/3 440-480/50-60Hz/3
1840 (72 1/2)	1840 (72 1/2)	1985 (78)	1985 (78)	2080 (82)	2250 (88 1/2)	2265 (89)
1660 (65 1/2)	2200 (86 1/2)	2100 (82 1/2)	2355 (92 3/4)	2400 (94 1/2)	2485 (97 3/4)	2665 (105)
1380 (54 1/4)	1380 (54 1/4)	1740 (68 1/2)	1740 (68 1/2)	1740 (68 1/2)	1940 (76 1/4)	2040 (80 1/4)
1140 (2515)	1360 (3000)	2600 (5750)	2810 (6200)	2990 (6595)	3550 (7830)	4990 (11000)
1280 (2825)	1510 (3330)	2760 (6085)	2970 (6550)	3150 (6950)	3760 (8290)	5310 (11710)
CE	CE	CE	CE	CE	CE	CE

To learn more, or to find a distributor in your area, visit UNIMAC.com

Alliance Laundry Systems – Shepard St, Ripon WI 54971 - 001 920 748 3121

Alliance International – Nieuwstraat 146, B-8560 Wevelgem, Belgium +32 56 41 20 54



UniMac is a division of Alliance Laundry Systems. Alliance is the world's leading manufacturer of commercial laundry equipment. Learn more at alliancelaundry.com

AI14-0050
©2014 Alliance Laundry Systems LLC



SERIOUS ABOUT LAUNDRY.